



DATA SHEET (Preliminary)

PB4010M5

- ◇ Low current rectification
- ◇ Low forward voltage
- ◇ ROHS Compliant
- ◇ UL-94 V-0 / Green EMC
- ◇ Matte Tin Lead finish (Pb-Free)

Device Marking Code	
PB4010M5	R4



Maximum Ratings (Ta = 25 °C)


Symbol	Parameter	Value	Units
P_D	Power Dissipation	250	mW
V_R	Reverse Voltage	40	V
$I_{F(AV)}$	Average Forward Current	1	A
I_{FSM}	Non-Repetitive Peak Forward Current *1	5	A
T_J	Junction Temperature	125	°C
T_{STG}	Storage Temperature	-55 to + 125	°C

*1: 8.3ms Single Half Sine-Wave


Electrical Characteristics (Ta = 25 °C Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
V_{BR}	Reverse Breakdown Voltage	$I_R=100\mu A$	40			V
I_R	Reverse Leakage Current	$V_R=10V$			30	μA
		$V_R=40V$			100	
V_F	Forward Voltage	$I_F=100mA$			0.39	V
		$I_F=500mA$			0.50	
		$I_F=700mA$			0.55	
		$I_F=1A$			0.60	

Typical Characteristics



Typical Instantaneous Forward Characteristics




Typical Reverse Leakage Characteristics

Ordering Information

Device	Package	Shipping	Tape wide	Emboss pitch	Tape specification	Notes
PB4010M5	DFN1006-2L	Tape & Reel 10000pcs /7" Reel	8mm	4mm	Conductive	

Package Dimensions



NOTICE

POPPULA'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS.

POPPULA reserve the right to make modifications enhancements improvements corrections or other changes without further notice to any product herein. POPPULA does not assume any liability arising out of the application or use of any product described herein.