



承 认 书
SPECIFICATION FOR APPROVAL

客户名称 Customer: _____

贵司料号 CUSTOMER P/N: _____

FFC cable 1.0mm 30P, total length 100mm, co-directional, gold finger 4mm, reinforcing plate 8mm

敝司料号 INTERIOR P/N: **FFC-1.0-30-100-A-4-8**

贵公司承认印 Approval signatures

料号/Part No.	签 章/Signatures

Send us a copy of reference, thank you! 日期 Date: _____

拟制/Drawn	李明
审核/Check	李军
批准/Approved	向军



Structure

NO	Project	Specification	Remark
1	Insulating film	Print 20624 Blank film 43um	60V 80C
2	Stiffeners	Blue 225um	PET
3	Conductor tinning	Thickness Width 0.035 0.3	± 0.005 ± 0.03
4	Conductor plating	Electroplate Electroplate	Tin Sn $\geq 40\mu$

Size

Number of conductor	N	30	
Spacing	P	1.0	± 0.05
Total spacing	Pt	29	± 0.08
Overall width	W	31	± 0.08
Edge width	M	1.0	± 0.08
Overall length	L	100	± 1.5
Mating thickness	T1	0.3	± 0.05
Thickness of the	T2	0.12	± 0.03
The inclination of the	A	-----	≤ 0.3
Punching inclination	B	-----	≤ 0.5
The length of the bare	S1/S2	4/4	≤ 0.05
Length of stiffener	B1/B2	8/8	± 1.5

Ancillary checklists

NO	Project	Specification	Quantity
1			
2			
3			

Precautions

1. The body image is for relationship comparison only, and everything is subject to the specifications of the data sheet.

1. Shelf life: 12 months for gold plating; 1m plating for 6
2. Storage environment: temperature 0°C-38°C; Humidity

Specifications and models: FFC-10-30-100-A-4-8

Customer part number: Customer model:

Version: What's Changed: date

A/O: New production: 2022/09/05

Name: FFC flexible Figure number: XP2022090501 Drawing: Lu ming
Proportion: FIT Unit: Millimetre(mm) Audit: Chen Jun
Vision: Page number: Page 1 of 1 Approved: Xiang Yu

东莞市讯普电子科技有限公司