



东莞市讯普电子科技有限公司

Dongguan Xunpu Electronic Technology Co., Ltd

承 认 书
SPECIFICATION FOR APPROVAL

客户名称 Customer: _____

贵司料号CUSTOMER P/N: _____

FFC cable 1.0mm 28P, total length 100mm, co-directional, gold finger 4mm, reinforcing plate 8mm

敝司料号INTERIOR P/N: FFC-1.0-28-100-A-4-8

贵公司承认印 Approval signatures

料号/Part No.	签章/Signatures

Send us a copy of reference, thank you!

日期 Date:

拟制/Drawn	李明
审核/Check	陈军
批准/Approved	向钰



Structure			
NO	Project	Specification	Remark
1	Insulating film	Print 20624 Blank film 43um	60V 80C
2	Stiffeners	Blue 225um	PET
3	Conductor trimming	Thickness 0.035 Width 0.3	±0.005 ±0.03
4	Conductor plating	Electroplate Tin Sn	≥40u"

Size			
Number of conductor	N	28	
Spacing	P	1.0	±0.05
Total spacing	Pt	27	±0.08
Overall width	W	29	±0.08
Edge width	M	1.0	±0.08
Overall length	L	100	±1.5
Mating thickness	T1	0.3	±0.05
Thickness of the	T2	0.12	±0.03
The inclination of the	A	—	≤0.3
Punching inclination	B	—	≤0.5
The length of the bare	S1/S2	4/4	±0.05
Length of stiffener	B1/B2	8/8	±1.5

Ancillary checklists			
NO	Project	Specification	Quantity
1			
2			
3			

Precautions

1. The body image is for relationship comparison only, and everything is subject to the specifications of the data sheet.

Specifications and models: FFC-1.0-28-100-A-4-8

Customer part number:	Customer model:
Version	What's Changed
A/O	New production
	date
	2022/09/05

XunPu 东莞市讯普电子科技有限公司

Name:	FFC flexible	Figure number:	XP2022090501	Drawing:	Li ming
Proportion:	1:1	Unit:	Millimetre(mm)	Audit:	Chen
Vision:	◆←	Page number:	Page 1 of 1	Approved:	Xiang Yu