DIELECTRIC LABORATORIES
a Knowles Precision Devices brand

knowles PRECISION DEVICES

14.5GHz Surface Mount Bandpass Filter

B145LB1S

www.knowlescapacitors.com

DESCRIPTION

DLI's surface mount catalog bandpass filters utilize DLI's low loss temperature stable materials which offer small size and minimal performance variation over temperature. The catalog BPF's are offered in a variety of frequency bands, which offers a drop in solution with highly repeatable performance.

FEATURES

- Small Size
- Fully Shielded Component
- Solder Surface Mount Package
- Moisture Sensitivity Level: MSL1
- Frequency Stable over Temperature
- Operating & Storage Temp: -55˚C to +125˚C
- Characteristic Impedance: 50Ω

Packaging and Ordering Information:

To request tape and reel packaging, please order part number B145LB1S-T

Certified System ISO 9001 QMI-SAI Global

Certified System AS 9100 QMI-SAI Global

RoHS 2015/863/EU Exemption-7a

SPECIFICATIONS*

Parameter	Frequency Range (GHz)	Min	Typ.	Max
Insertion Loss (dB)	14.1 - 14.9	2.75	3.0	3.5
Return Loss (dB)		10.0	14.0	
Low Side Rejection (dB)	DC - 11.75	60.0	65.0	
High Side Rejection (dB)	16.5 - 19.5	60.0	65.0	
CW Input Power (W)**				5
θ_{JC} $\left(\frac{°C}{W}\right)$	15			
Size (L x W x H)	0.550 x 0.230 x 0.093 in 13.97 x 5.84 x 2.36 mm			

*Electrical specifications based on typical probed performance at room temperature. Insertion loss shall vary ±0.5dB over temperature.

**Power rating assumes the component will be mounted to a PCB with good thermally conducting ground vias as outlined in the recommended PCB layout that are connected to an adequate heat sink. Max power is based on 125°C base temperature.

Information in this document is for informational and guideline purposes only. All information regarding the Product described in this datasheet is subject to change from time to time at Knowles Precision Devices' sole discretion. It is the customer's sole responsibility to evaluate the suitability of the Product in the customer's particular application. Knowles Precision Devices assumes no responsibility or liability for the use of the information contained within.


2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710

To Order Contact KCCSales@knowles.com | For Technical Inquiries Contact DLIengineering@knowles.com

14.5GHz Surface Mount Bandpass Filter

B145LB1S

Typical Measured Performance



*Typical de-embedded measured performance mounted on a connectorized test fixture. DEB is 0.010in RO4350B with 50.0Ohm CPW ground traces going into the ports at room temperature.

14.5GHz Surface Mount Bandpass Filter

B145LB1S

www.knowlescapacitors.com


Physical Dimensions

Units = inches


Top View




Side View



End View



Bottom View



Notes :

1. Termination Finish:

ENIG: 3 - 6 µinch Au over 50 µinch Ni


2. Maximum Assembly Process Temperature: 250°C

Tolerances:

For values with 3 decimal places ±0.001

For values with 4 decimal places ±0.0005

DETAIL A
(2 PLACES)




2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710

To Order Contact KCCSales@knowles.com | For Technical Inquiries Contact DLIengineering@knowles.com

Recommended PCB Layout


Unit = mils



PCB RECOMMENDED STACKUP

Filter is matched to RF layer stackup seen below
Dimensions are specified below in inches (not to scale)

Board material	:	RO4350b
Board material design dk	:	3.66
CPWG	:	20mil trace width, 15mil gaps



For further details and best practices, reference the **Microwave Products Guide,** available at: https://www.knowlescapacitors.com/Support/Catalogs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Knowles:

B145LB1S-T B145LB1S