



MPCM301X, MPCM302X, MPCM305X Series

SOP4, DC Input, Random-Phase Photo TRIAC Photo Coupler

■ Features

- High isolation 3750 VRMS
- DC input with random-phase photo triac output
- Operating temperature range - 40 °C to 100 °C
- RoHS & REACH Compliance
- Halogen free
- MSL class 1
- Regulatory Approvals
 - UL - UL1577
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1-2022

■ Applications


- Solenoid/valve controls
- Lighting controls
- Motor controls
- Temperature controls
- Static AC power switches
- Solid state relays
- Interfacing microprocessors to 115 to 240VAC peripherals

■ Description

The MPCM301X, MPCM302X and MPCM305X series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon random-phase photo triac in a plastic SOP4 package.

With the robust coplanar double mold structure, MPCM301X, MPCM302X and MPCM305X series provide the most stable isolation feature.

■ Schematic





MPCM301X, MPCM302X, MPCM305X Series

SOP4, DC Input, Random-Phase Photo TRIAC Photo Coupler

ABSOLUTE MAXIMUM RATINGS					
PARAMETER		SYMBOL	VALUE	UNIT	NOTE
INPUT					
Forward Current		I _F	60	mA	
Reverse Voltage		V _R	6	V	
Junction Temperature		T _j	125	°C	
Input Power Dissipation		P _I	100	mW	
OUTPUT					
Off-state Output Terminal Voltage	MPCM301X	V _{DRM}	250	V	
	MPCM302X		400		
	MPCM305X		600		
Peak Repetitive Surge Current PW=100μs, 120pps		I _{TSM}	1	A	
Junction Temperature		T _j	125	°C	
Output Power Dissipation		P _O	300	mW	
COMMON					
Total Power Dissipation		P _{tot}	330	mW	
Isolation Voltage		V _{iso}	3750	V _{rms}	1
Operating Temperature		T _{opr}	-40~100	°C	
Storage Temperature		T _{stg}	-55~125	°C	
Soldering Temperature		T _{sol}	260	°C	2

Note 1. AC For 1 Minute, R.H. = 40 ~ 60%

Note 2. For 10 seconds



MPCM301X, MPCM302X, MPCM305X Series

SOP4, DC Input, Random-Phase Photo TRIAC Photo Coupler

ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C							
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
INPUT							
Forward Voltage	V _F	-	1.24	1.4	V	I _F =10mA	
Reverse Current	I _R	-	-	10	μA	V _R =6V	
Input Capacitance	C _{in}	-	8.5	250	pF	V=0, f=1kHz	
OUTPUT							
Peak Off-state Current, Either Direction	I _{DRM}	-	-	100	nA	V _{DRM} =Rated V _{DRM} I _F =0	3
Peak On-state Voltage, Either Direction	V _{TM}	-	1.58	2.5	V	I _{TM} =100mA I _F =Rated I _{FT}	
Critical Rate of Rise of Off-state Voltage	dV/dt	1000	-	-	V/μs	V _{PEAK} =Rated V _{DRM}	4
TRANSFER CHARACTERISTICS							
LED Trigger Current	MPCM3010, MPCM3021, MPCM3051	I _{FT}	-	-	15	Terminal Voltage = 3V I _{TM} =100mA	
	MPCM3011, MPCM3022, MPCM3052		-	-	10		
	MPCM3012, MPCM3023, MPCM3053		-	-	5		
Holding Current	I _H	-	257	-	μA		
Isolation Resistance	R _{iso}	10 ¹²	10 ¹⁴	-	Ω	DC500V, 40 ~ 60% R.H.	
Floating Capacitance	C _{io}	-	0.4	1	pF	V=0, f=1MHz	

Note3. Test voltage must be applied within dV/dt rating.

Note4. Refer to Fig.15 & Fig.16

CHARACTERISTIC CURVES




Fig.1 Forward Current vs. Ambient Temperature




Fig.2 On-state Terminal Current vs. Ambient Temperature




Fig.3 Forward Current vs. Forward Voltage




Fig.4 Off-state Terminal Current vs. Ambient Temperature




Fig.5 Normalized Off-state Terminal Voltage vs. Ambient Temperature




Fig.6 Normalized Trigger Current vs. LED Trigger Pulse Width

CHARACTERISTIC CURVES




Fig.7 Normalized Trigger Current vs. Ambient Temperature




Fig.8 On-state Terminal Voltage vs. Ambient Temperature




Fig.9 On-state Terminal Voltage vs. On-state Terminal Current




Fig.10 Holding Current vs. Ambient Temperature




Fig.11 Turn On Time vs. Forward Current




Fig.12 Turn On Time vs. Ambient Temperature

TEST CIRCUITS

Fig.13 Test Circuits of Turn On Time




Fig.14 Waveforms of Turn On Time




Fig.15 Test Circuits of dV/dt







Fig.16 Waveforms of dV/dt



PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)




Recommended Solder Mask (Dimensions in mm unless otherwise stated)




CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option T1



Option T2






MPCM301X, MPCM302X, MPCM305X Series

SOP4, DC Input, Random-Phase Photo TRIAC Photo Coupler

ORDERING AND MARKING INFORMATION

MARKING INFORMATION

	MPC : Company Abbr. 30XX : Part Number & Rank V : VDE Option Y : Fiscal Year A : Manufacturing Code WW : Work Week
---	--

ORDERING INFORMATION

MPCM30XX(Z)-GV


MPC – Company Abbr.
M – Package Type: SOP4
30XX – Part Number & Rank(10/11/12/21/22/23/51/52/53)
Z – Tape and Reel Option (T1/T2)
G – Material Option (G: Green, None: Non-Green)
V – VDE Option (V or None)

PACKING QUANTITY

Option	Quantity	Quantity – Inner box	Quantity – Outer box
T1	3000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 45k Units
T2	3000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 45k Units

REFLOW INFORMATION


REFLOW PROFILE



Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (Tsmin)	100	150°C
Temperature Max. (Tsmax)	150	200°C
Time (ts) from (Tsmin to Tsmax)	60-120 seconds	60-120 seconds
Ramp-up Rate (tL to tP)	3°C/second max.	3°C/second max.
Liquidous Temperature (TL)	183°C	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (tP) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.

TEMPERATURE PROFILE OF SOLDERING

WAVE SOLDERING (JESD22-A111 COMPLIANT)



HAND SOLDERING BY SOLDERING IRON

Soldering Temperature	380+0/-5°C
Soldering Time	3 sec max.

- One time soldering is recommended for all soldering method.
- Do not solder more than three times for IR reflow soldering.



MPCM301X, MPCM302X, MPCM305X Series

SOP4, DC Input, Random-Phase Photo TRIAC Photo Coupler

DISCLAIMER

- Our company is continually improving the quality, reliability, function and design. Our company reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Immerge unit's body in solder paste is not recommended.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.

■ **Revision History**

Version	Date	Subjects (major changes since last revision)
1.0	2018-12-21	Datasheet Complete
1.1	2023-07-05	Upgrade Datasheet