

SS12 THRU SS110

Surface Mount Schottky Barrier Rectifiers

Reverse Voltage - 20 to 100 V


Forward Current - 1 A

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- For surface mounted applications
- Metal silicon junction, majority carrier conduction
- Built-in strain relief, ideal for automated placement
- Low power loss, high efficiency.
- High forward surge current capability

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Mechanical Data

- **Case:** SMA (DO-214AC) molded plastic body
- **Terminals:** leads solderable per MIL-STD-750, Method 2026
- **Polarity:** color band denotes cathode end


Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	SS12	SS13	SS14	SS15	SS16	SS18	SS110	Unit
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	80	100	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	56	70	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	80	100	V
Maximum Average Forward Rectified Current	I _{F(AV)}	1							A
Peak Forward Surge Current 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	30							A
Maximum Instantaneous Forward Voltage at 1 A	V _F	0.55			0.75		0.85		V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	0.5 20							mA
Typical Junction Capacitance ¹⁾	C _j	110							pF
Typical Thermal Resistance ²⁾	R _{θJA}	90							°C/W
Operating Junction Temperature Range	T _j	- 55 to + 125							°C
Storage Temperature Range	T _{stg}	- 55 to + 150							°C

¹⁾ Measured at 1MHz and applied reverse voltage of 4 V D.C.

²⁾ P.C.B. mounted with 2" X 2" (5 X 5 cm) copper pad areas.



SS12 THRU SS110

Electrical Characteristic Curves

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current







Fig.6- Typical Transient Thermal Impedance




SS12 THRU SS110

Package Outline Dimensions in inches (millimeters)

SMA(DO-214AC)



Recommended Soldering Footprint




Marking information

" SS1** " = Part No.

Type	Marking	Type	Marking	Type	Marking	Type	Marking
SS12	SS12	SS13	SS13	SS14	SS14	SS15	SS15
SS16	SS16	SS18	SS18	SS110	SS110		

" III " = Cathode line

Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.

