



承 认 书
SPECIFICATION FOR APPROVAL

客户名称 Customer: _____

贵司料号 CUSTOMER P/N: _____

FFC cable 1.0mm 50P, total length 100mm, co-directional, gold finger 4mm, reinforcing plate 8mm

敝司料号 INTERIOR P/N: **FFC-1.0-50-100-A-4-8**

贵公司承认印 Approval signatures

料号/Part No.	签 章/Signatures

Send us a copy of reference, thank you! 日期 Date: _____

拟制/Drawn	李明
审核/Check	李军
批准/Approved	向伟



Technical drawing of a flexible circuit board showing top and side views with dimensions S1, S2, B1, B2, A, and B. Labels include "Printing insulating film", "Stiffeners", "Conductor", and "White insulating film".

Structure			
NO	Project	Specification	Remark
1	Insulating film	Print 20624 Blank film	43um 60V 80C
2	Stiffeners	Blue	225um PET
3	Conductor tinning	Thickness Width	0.035 0.3 ±0.005 ±0.03
4	Conductor plating	Electroplate Electroplate	Tin Sn ≥40μ

Size			
Number of conductor	N	50	
Spacing	P	1.0	±0.05
Total spacing	Pt	49	±0.08
Overall width	W	51	±0.08
Edge width	M	1.0	±0.08
Overall length	L	100	±1.5
Mating thickness	T1	0.3	±0.05
Thickness of the	T2	0.12	±0.03
The inclination of the	A	-----	≤0.3
Punching inclination	B	-----	≤0.5
The length of the bare	S1/S2	4/4	±0.05
Length of stiffener	B1/B2	8/8	±1.5

Ancillary checklists			
NO	Project	Specification	Quantity
1			
2			
3			

Precautions

1. The body image is for relationship comparison only, and everything is subject to the specifications of the data sheet.

1. Shelf life: 12 months for gold plating; 1m plating for 6
2. Storage environment: temperature 0°C-38°C; Humidity

Specifications and models:	FFC-10-50-100-A-4-8		
Customer part number:	Customer model:		
Version	What's Changed	date	
A/O	New production	2022/09/05	

XunPu 东莞市讯普电子科技有限公司

Name:	FFC flexible	Figure number:	XP2022090501	Drawing:	Li ming
Proportion:	1:1	Unit:	Millimetre(mm)	Audit:	Chen Jun
Vision:	◆ ←	Page number:	Page 1 of 1	Approved:	Xiang Yu