Notice for TAIYO YUDEN Products

Please read this notice before using the TAIYO YUDEN products.

⚠ REMINDERS

Product Information in this Catalog

Product information in this catalog is as of March 2023. All of the contents specified herein and production status of the products listed in this catalog are subject to change without notice due to technical improvement of our products, etc. Therefore, please check for the latest information carefully before practical application or use of our products.

Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in this catalog or individual product specification sheets.

Approval of Product Specifications

Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available. When using our products, please be sure to approve our product specifications or make a written agreement on the product specification with TAIYO YUDEN in advance.

Pre-Evaluation in the Actual Equipment and Conditions

Please conduct validation and verification of our products in actual conditions of mounting and operating environment before using our products.

Limited Application

1. Equipment Intended for Use

The products listed in this catalog are intended for general-purpose and standard use in general electronic equipment for consumer (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and other equipment specified in this catalog or the individual product specification sheets, or the equipment approved separately by TAIYO YUDEN.
TAIYO YUDEN has the product series intended for use in the following equipment. Therefore, when using our products for these equipment, please check available applications specified in this catalog or the individual product specification sheets and use the corresponding products.

Application	Product Series		Quality Grade *3
	Equipment *1	Category (Part Number Code *2)	
Automotive	Automotive Electronic Equipment (POWERTRAIN, SAFETY)	A	1
	Automotive Electronic Equipment (BODY & CHASSIS, INFOTAINMENT)	C	2
Industrial	Telecommunications Infrastructure and Industrial Equipment	B	2
Medical	Medical Devices classified as GHTF Class C (Japan Class III)	M	2
	Medical Devices classified as GHTF Classes A or B (Japan Classes I or II)	L	3
Consumer	General Electronic Equipment	S	3
	Only for Mobile Devices *4	E	4

*Notes: 1. Based on the general specifications required for electronic components for such equipment, which are recognized by TAIYO YUDEN, the use of each product series for the equipment is recommended. Please be sure to contact TAIYO YUDEN before using our products for equipment other than those covered by the product series.
2. On each of our part number, the 2nd code from the left is a code indicating the “Category” as shown in the above table. For details, please check the explanatory materials regarding the part numbering system of each of our products.
3. Each product series is assigned a “Quality Grade” from 1 to 4 in order of higher quality. Please do not incorporate a product into any equipment with a higher Quality Grade than the Quality Grade of such product without the prior written consent of TAIYO YUDEN.
4. The applications covered by this product series are limited to mobile devices (smartphone, tablet PC, smartwatch, handheld game console, etc.) among general electronic equipment for consumer. The design, specifications and operating environment, etc. differ from those of the product series for "General Electronic Equipment" (Category: S), so please check the individual product specification sheets for details. The product series for "General Electronic Equipment" (Category: S) can also be used for mobile devices.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/) .

2. Equipment Requiring Inquiry

Please be sure to contact TAIYO YUDEN for further information before using the products listed in this catalog for the following equipment (excluding intended equipment as specified in this catalog or the individual product specification sheets) which may cause loss of human life, bodily injury, serious property damage and/or serious public impact due to a failure or defect of the products and/or malfunction attributed thereto.

(1) Transportation equipment (automotive powertrain control system, train control system, and ship control system, etc.)
(2) Traffic signal equipment
(3) Disaster prevention equipment, crime prevention equipment
(4) Medical devices classified as GHTF Class C (Japan Class III)
(5) Highly public information network equipment, data-processing equipment (telephone exchange, and base station, etc.)
(6) Any other equipment requiring high levels of quality and/or reliability equal to the equipment listed above

3. Equipment Prohibited for Use

Please do not incorporate our products into the following equipment requiring extremely high levels of safety and/or reliability.

(1) Aerospace equipment (artificial satellite, rocket, etc.)
(2) Aviation equipment *1
(3) Medical devices classified as GHTF Class D (Japan Class IV), implantable medical devices *2
(4) Power generation control equipment (nuclear power, hydroelectric power, thermal power plant control system, etc.)
(5) Undersea equipment (submarine repeating equipment, etc.)
(6) Military equipment
(7) Any other equipment requiring extremely high levels of safety and/or reliability equal to the equipment listed above

*Notes: 1. There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

2. Implantable medical devices contain not only internal unit which is implanted in a body, but also external unit which is connected to the internal unit.

4. Limitation of Liability

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the products listed in this catalog for any equipment that is not intended for use by TAIYO YUDEN, or any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

Safety Design

When using our products for high safety and/or reliability-required equipment or circuits, please fully perform safety and/or reliability evaluation. In addition, please install (i) systems equipped with a protection circuit and a protection device and/or (ii) systems equipped with a redundant circuit or other system to prevent an unsafe status in the event of a single fault for a failsafe design to ensure safety.

Intellectual Property Rights

Information contained in this catalog is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.

Limited Warranty

Please note that the scope of warranty for our products is limited to the delivered our products themselves conforming to the product specifications specified in the individual product specification sheets, and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a failure or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement, provided, however, that our products shall be used for general-purpose and standard use in the equipment specified in this catalog or the individual product specification sheets.

TAIYO YUDEN's Official Sales Channel

The contents of this catalog are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this catalog are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.

Caution for Export

Some of our products listed in this catalog may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/) .

Industrial Application Guide

We have the product series (the 2nd code from the left side of the part number is “B”) intended for use in telecommunications infrastructure and industrial equipment (its typical examples are as shown in the table below). Therefore, when using our products for these equipment, please check it carefully by referring to the part number or the individual product specification sheets and use the corresponding product series. Should you have any questions on this matter, please contact us.

Product Series (The 2nd Code from the Left Side of the Part Number)	Category	Telecommunications Infrastructure and Industrial Equipment (Typical Example)
B	Telecommunications Infrastructure	• Base Station • Optical Transceiver • Router/Switch (Carrier-Grade) • UPS (Uninterruptible Power Supply), etc.
	Factory Automation	• PLC (Programmable Logic Controller) • Servomotor/Servo Driver • Industry Robot, etc.
	Measurement	• Gas Meter • Water Meter • Flow Meter • Pressure Gauge Meter • Magnetometer • Thermometer, etc.
	Electric Power Apparatus	• Power Conditioner (Solar Power System) • Smart Meter • GFCI (Ground Fault Circuit Interrupter) • Electric Vehicle Charging Station, etc.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/) .

Wire-wound Ferrite Bead Inductors for Power Lines LBMC/LBMG series for Telecommunications Infrastructure and Industrial Equipment

Code in front of Series have been extracted from Part number, which describes the segment of products, such as kinds and characteristics.

REFLOW

■PART NUMBER

*Operating Temp. : −40～125℃(Including self-generated heat)

L B M C	C	3 2 1 6	1 1	T	8 0 0	R	G
①	②	③	④	⑤	⑥	⑦	⑧

①Series

Code (1)(2)(3)(4)	
LBMC	Wire-wound Ferrite Bead Inductors for Power Lines for Telecommunications Infrastructure and Industrial Equipment
LBMG	Wire-wound Ferrite Bead Inductors for Power Lines for Telecommunications Infrastructure and Industrial Equipment

(1) Product Group

Code	
L	Inductors

(2) Category

Code	Recommended equipment	Quality Grade
B	Telecommunications Infrastructure and Industrial Equipment	2

(3) Type

Code	
M	Ferrite Wire-wound bead

(4) Features, Characteristics

Code	
C	High current
G	High frequency

②Features

Code	Feature
A	Standard(20MHz)
C	Wave-shaping
G	For GHz noise

③Dimensions(L×W)

Code	Type(inch)	Dimensions(L×W) [mm]
1608	1608(0603)	1.6×0.8
2012	2012(0805)	2.0×1.25
2016	2016(0806)	2.0×1.6
3216	3216(1206)	3.2×1.6
3225	3225(1210)	3.2×2.5
4516	4516(1806)	4.5×1.6
4525	4525(1810)	4.5×2.5

④Dimensions(T)

Code	Dimensions(T)[mm]
08	0.8
	0.85
11	1.1
16	1.6
25	2.5

⑤Packaging

Code	Packaging
T	Taping

⑥Nominal impedance


Code (example)	Nominal impedance[Ω]
330	33
221	220
102	1000

⑦Impedance tolerance


Code	Impedance tolerance
R	±25%
N	±30%

⑧Internal code

■STANDARD EXTERNAL DIMENSIONS / STANDARD QUANTITY



Recommended Land Patterns
Surface Mounting
・Mounting and soldering conditions should be checked beforehand.



Type	A	B	C
1608	1.0	1.0	1.0
2012	1.4	1.2	1.65
2016	1.4	1.2	2.0
3216	1.4	2.2	2.0
3225	1.4	2.2	2.9
4516	1.75	3.5	2.0
4525	1.75	3.5	2.9

Unit : mm

Type	L	W	T	e	Standard quantity [pcs]	
					Paper tape	Embossed tape
160808 *1 (0603)	1.6±0.2 (0.063±0.008)	0.8±0.2 (0.031±0.008)	0.8±0.2 (0.031±0.008)	0.3±0.2 (0.012±0.008)	4000	—
160808 *2 (0603)	1.6±0.1 (0.063±0.004)	0.8±0.1 (0.031±0.004)	0.8±0.1 (0.031±0.004)	0.3±0.15 (0.012±0.006)	4000	—
201208 (0805)	2.0±0.2 (0.079±0.008)	1.25±0.2 (0.049±0.008)	0.85±0.2 (0.033±0.008)	0.5±0.3 (0.020±0.012)	4000	—
201616 (0806)	2.0±0.2 (0.079±0.008)	1.6±0.2 (0.063±0.008)	1.6±0.2 (0.063±0.008)	0.5±0.3 (0.020±0.012)	—	2000
321611 (1206)	3.2±0.3 (0.126±0.012)	1.6±0.2 (0.063±0.008)	1.1±0.2 (0.043±0.008)	0.5±0.3 (0.020±0.012)	—	2000
321616 (1206)	3.2±0.3 (0.126±0.012)	1.6±0.2 (0.063±0.008)	1.6±0.2 (0.063±0.008)	0.5±0.3 (0.020±0.012)	—	2000
322525 (1210)	3.2±0.3 (0.126±0.012)	2.5±0.3 (0.098±0.012)	2.5±0.3 (0.098±0.012)	0.5±0.3 (0.020±0.012)	—	1000
451611 (1806)	4.5±0.3 (0.177±0.012)	1.6±0.2 (0.063±0.008)	1.1±0.2 (0.043±0.008)	0.5±0.3 (0.020±0.012)	—	2000
451616 (1806)	4.5±0.3 (0.177±0.012)	1.6±0.2 (0.063±0.008)	1.6±0.2 (0.063±0.008)	0.5±0.3 (0.020±0.012)	—	2000
452525 (1810)	4.5±0.4 (0.177±0.016)	2.5±0.3 (0.098±0.012)	2.5±0.3 (0.098±0.012)	0.9±0.6 (0.035±0.024)	—	1000

*1 LBMC, *2 LBMG

Unit : mm (inch)

▸ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (http://www.ty-top.com/) .

■PART NUMBER

・All the Wire-wound Ferrite Bead Inductors for Power Lines of the catalog lineup are RoHS compliant.

Notes)
・The exchange of individual specifications is necessary depending on your application and/or circuit condition. Please contact TAIYO YUDEN's official sales channel.
・The products are for Telecommunications infrastructure and Industrial equipment.
Please consult with TAIYO YUDEN's official sales channel for the details of the product specifications, etc., and please review and approve the product specifications before ordering.

Standard type

●2012(0805) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMCC201208T250NG	FB MJ2125HS250NT8	25	±30%	100	0.004	6.0	0.85 ±0.2
LBMCC201208T420RG	FB MJ2125HS420-T8	42	±25%	100	0.008	4.0	0.85 ±0.2
LBMCA201208T210NG	FB MJ2125HM210NT8	21	±30%	100	0.004	6.0	0.85 ±0.2
LBMCA201208T330RG	FB MJ2125HM330-T8	33	±25%	100	0.008	4.0	0.85 ±0.2
LBMCG201208T8R0NG	FB MJ2125HL8R0NT8	8	±30%	100	0.008	4.0	0.85 ±0.2

●3216(1206) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMCC321611T480NG	FB MJ3216HS480NT8	48	±30%	100	0.005	6.0	1.1 ±0.2
LBMCC321611T800RG	FB MJ3216HS800-T8	80	±25%	100	0.010	4.0	1.1 ±0.2
LBMCA321611T380NG	FB MJ3216HM380NT8	38	±30%	100	0.005	6.0	1.1 ±0.2
LBMCA321611T600RG	FB MJ3216HM600-T8	60	±25%	100	0.010	4.0	1.1 ±0.2
LBMCG321611T160NG	FB MJ3216HL160NT8	16	±30%	100	0.012	4.0	1.1 ±0.2

●4516(1806) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMCC451611T720NG	FB MJ4516HS720NT8	72	±30%	100	0.007	6.0	1.1 ±0.2
LBMCC451611T111RG	FB MJ4516HS111-T8	110	±25%	100	0.014	4.0	1.1 ±0.2
LBMCA451611T560NG	FB MJ4516HM560NT8	56	±30%	100	0.007	6.0	1.1 ±0.2
LBMCA451611T900RG	FB MJ4516HM900-T8	90	±25%	100	0.014	4.0	1.1 ±0.2
LBMCG451611T230NG	FB MJ4516HL230NT8	23	±30%	100	0.014	3.5	1.1 ±0.2

High impedance type(GHz Band)

●1608(0603) type

New part number	Old part number (for reference)	Nominal impedance Measuring frequency 100[MHz]		Nominal impedance Measuring frequency 1[GHz]		DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
		(Ω)	tolerance	(Ω)	tolerance			
LBMGA160808T470RG	FB MH1608HM470-T8	47	±25%	75	±40%	0.020	3.5	0.8 ±0.1
LBMGA160808T600RG	FB MH1608HM600-T8	60	±25%	100	±40%	0.025	3.0	0.8 ±0.1
LBMGA160808T101RG	FB MH1608HM101-T8	100	±25%	170	±40%	0.035	2.5	0.8 ±0.1
LBMGA160808T151RG	FB MH1608HM151-T8	150	±25%	270	±40%	0.050	2.1	0.8 ±0.1
LBMGA160808T221RG	FB MH1608HM221-T8	220	±25%	370	±40%	0.070	1.8	0.8 ±0.1
LBMGA160808T331RG	FB MH1608HM331-T8	330	±25%	520	±40%	0.130	1.2	0.8 ±0.1
LBMGA160808T471RG	FB MH1608HM471-T8	470	±25%	750	±40%	0.150	1.0	0.8 ±0.1
LBMGA160808T601RG	FB MH1608HM601-T8	600	±25%	900	±40%	0.170	0.9	0.8 ±0.1
LBMGA160808T102RG	FB MH1608HM102-T8	1000	±25%	1200	±40%	0.350	0.6	0.8 ±0.1
LBMGG160808T300RG	FB MH1608HL300-T8	30	±25%	120	±40%	0.028	2.6	0.8 ±0.1
LBMGG160808T600RG	FB MH1608HL600-T8	60	±25%	220	±40%	0.045	2.1	0.8 ±0.1
LBMGG160808T121RG	FB MH1608HL121-T8	120	±25%	540	±40%	0.130	1.2	0.8 ±0.1
LBMGG160808T221RG	FB MH1608HL221-T8	220	±25%	950	±40%	0.170	0.9	0.8 ±0.1
LBMGG160808T331RG	FB MH1608HL331-T8	330	±25%	1200	±40%	0.210	0.8	0.8 ±0.1
LBMGG160808T471RG	FB MH1608HL471-T8	470	±25%	1500	±40%	0.350	0.6	0.8 ±0.1
LBMGG160808T601RG	FB MH1608HL601-T8	600	±25%	1800	±40%	0.450	0.5	0.8 ±0.1

※)The rated current is the value of current at which the temperature of the element is increased by 40 deg.

■PART NUMBER

High impedance type

●2012(0805) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMGA201208T800RG	FB MH2012HM800-T8	80	±25%	100	0.025	2.7	0.85 ±0.2
LBMGA201208T121RG	FB MH2012HM121-T8	120	±25%	100	0.032	2.5	0.85 ±0.2
LBMGA201208T221RG	FB MH2012HM221-T8	220	±25%	100	0.060	2.0	0.85 ±0.2
LBMGA201208T331RG	FB MH2012HM331-T8	330	±25%	100	0.080	1.8	0.85 ±0.2

●2016(0806) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMGA201616T121NG	FB MH2016HM121NT8	120	±30%	100	0.015	4.5	1.6 ±0.2
LBMGA201616T251NG	FB MH2016HM251NT8	250	±30%	100	0.050	2.0	1.6 ±0.2

●3216(1206) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMGA321616T221NG	FB MH3216HM221NT8	220	±30%	100	0.020	4.0	1.6 ±0.2
LBMGA321616T501NG	FB MH3216HM501NT8	500	±30%	100	0.070	2.0	1.6 ±0.2

●3225(1210) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMGA322525T601NG	FB MH3225HM601NT8	600	±30%	100	0.042	3.0	2.5 ±0.3
LBMGA322525T102NG	FB MH3225HM102NT8	1000	±30%	100	0.100	2.0	2.5 ±0.3
LBMGA322525T202NG	FB MH3225HM202NT8	2000	±30%	100	0.130	1.2	2.5 ±0.3

●4516(1806) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMGA451616T851NG	FB MH4516HM851NT8	850	±30%	100	0.100	1.5	1.6 ±0.2

●4525(1810) type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMGA452525T102NG	FB MH4525HM102NT8	1000	±30%	100	0.060	3.0	2.5 ±0.3
LBMGA452525T162NG	FB MH4525HM162NT8	1600	±30%	100	0.130	2.0	2.5 ±0.3

●High current type

New part number	Old part number (for reference)	Nominal impedance (Ω)	Impedance tolerance	Measuring frequency [MHz]	DC Resistance [Ω](max.)	Rated current [A](max.)	Thickness [mm]
LBMCC160808T220NG	FB MJ1608HS220NT8	22	±30%	100	0.004	7.5	0.8 ±0.2
LBMCC160808T280NG	FB MJ1608HS280NT8	28	±30%	100	0.006	6.0	0.8 ±0.2
LBMCA160808T180NG	FB MJ1608HM180NT8	18	±30%	100	0.004	7.5	0.8 ±0.2
LBMCA160808T230NG	FB MJ1608HM230NT8	23	±30%	100	0.006	6.0	0.8 ±0.2


※)The rated current is the value of current at which the temperature of the element is increased by 40 deg.

ELECTRICAL CHARACTERISTICS


Standard type

2012 type


LBMCC201208T250NG




LBMCC201208T420RG




LBMCA201208T210NG



LBMCA201208T330RG




LBMCG201208T8R0NG




3216 type


LBMCC321611T480NG




LBMCC321611T800RG



LBMCA321611T380NG




LBMCA321611T600RG




4516 type


LBMCG321611T160NG




LBMCC451611T720NG




LBMCC451611T111RG




LBMCA451611T560NG



LBMCA451611T900RG



LBMCG451611T230NG




▸ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (http://www.ty-top.com/) .

ELECTRICAL CHARACTERISTICS


High impedance type(GHz Band)

1608 type


LBMGA160808T470RG




LBMGA160808T600RG




LBMGA160808T101RG




LBMGA160808T151RG




LBMGA160808T221RG




LBMGA160808T331RG




LBMGA160808T471RG




LBMGA160808T601RG




LBMGA160808T102RG




LBMGG160808T300RG




LBMGG160808T600RG




LBMGG160808T121RG




LBMGG160808T221RG



LBMGG160808T331RG




LBMGG160808T471RG



ELECTRICAL CHARACTERISTICS


LBMGG160808T601RG




High impedance type

2012 type


LBMGA201208T800RG




LBMGA201208T121RG



LBMGA201208T221RG




LBMGA201208T331RG




2016 type

LBMGA201616T121NG




LBMGA201616T251NG




3216 type

LBMGA321616T221NG




LBMGA321616T501NG




3225 type


LBMGA322525T601NG



LBMGA322525T102NG




LBMGA322525T202NG




4516 type


LBMGA451616T851NG




■ELECTRICAL CHARACTERISTICS


■4525 type







■High current type










■Derating of Rated Current

●LBMC/LBMG sereise

Derating of current is necessary for LBMC/LBMG series depending on ambient temperature.
Please refer to the chart shown below for appropriate derating of current.



Wire-wound Ferrite Bead Inductors for Power Lines LSMC/LSMG/LAMG/LCMC/LCMG/LBMC/LBMG/ LLMC/LLMG/LMMC/LMMG series


■PACKAGING

①Minimum Quantity


Type	Standard Quantity[pcs]	
	Paper Tape	Embossed Tape
1608(0603)	4000	—
2125(0805)	4000	—
2012(0805)	4000	—
2016(0806)	—	2000
3216(1206)	—	2000
3225(1210)	—	1000
4516(1806)	—	2000
4525(1810)	—	1000
4532(1812)	—	2000

②Tape Material

●Card board carrier tape




●Embossed tape



③Taping Dimensions

●Paper tape (0.315 inches wide)




▸ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (http://www.ty-top.com/) .

Type	Chip Cavity		Insertion Pitch	Tape Thickness
	A	B	F	T
1608 (0603)	1.0±0.2 (0.039±0.008)	1.8±0.2 (0.071±0.008)	4.0±0.2 (0.157±0.008)	1.1max (0.043max)
2012 (0805)	1.5±0.2 (0.059±0.008)	2.3±0.2 (0.091±0.008)	4.0±0.2 (0.157±0.008)	1.1max (0.043max)

Unit : mm(inch)

●Embossed tape (0.315 inches wide)




Type	Chip Cavity		Insertion Pitch	Tape Thickness	
	A	B	F	K	T
2016 (0806)	1.8±0.2 (0.071±0.008)	2.2±0.2 (0.087±0.008)	4.0±0.2 (0.157±0.008)	2.6max (0.102max)	0.6max (0.024max)
3216 ＊1 (1206)	1.9±0.2 (0.075±0.008)	3.5±0.2 (0.138±0.008)	4.0±0.2 (0.157±0.008)	1.5max (0.059max)	0.3max (0.012max)
3216 ＊2 (1206)	1.9±0.2 (0.075±0.008)	3.5±0.2 (0.138±0.008)	4.0±0.2 (0.157±0.008)	2.6max (0.102max)	0.6max (0.024max)
3225 (1210)	2.8±0.2 (0.110±0.008)	3.5±0.2 (0.138±0.008)	4.0±0.2 (0.157±0.008)	4.0max (0.157max)	0.6max (0.024max)

＊1 LSMC/LCMC/LBMC/LLMC/LMMC

＊2 LSMG/LAMG/LCMG/LBMG/LLMG/LMMG

Unit : mm(inch)

●Embossed tape (0.472 inches wide)




Type	Chip Cavity		Insertion Pitch	Tape Thickness	
	A	B	F	K	T
4516 ＊1 (1806)	1.9±0.2 (0.075±0.008)	4.9±0.2 (0.193±0.008)	4.0±0.2 (0.157±0.008)	1.5max (0.059max)	0.3max (0.012max)
4516 ＊2 (1806)	1.9±0.2 (0.075±0.008)	4.9±0.2 (0.193±0.008)	4.0±0.2 (0.157±0.008)	2.6max (0.102max)	0.6max (0.024max)
4525 (1810)	2.9±0.2 (0.114±0.008)	4.9±0.2 (0.193±0.008)	4.0±0.2 (0.157±0.008)	4.0max (0.157max)	0.6max (0.024max)
4532 (1812)	3.6±0.2 (0.142±0.008)	4.9±0.2 (0.193±0.008)	8.0±0.2 (0.315±0.008)	4.0max (0.157max)	0.6max (0.024max)

＊1 LSMC/LCMC/LBMC/LLMC/LMMC

＊2 LSMG/LAMG/LCMG/LBMG/LLMG/LMMG


Unit : mm(inch)

④Leader and Blank portion



Insertion leader is 400 mm or more (including 20 empty cavities)
Empty cavities at end of reel: 40 holes or more


⑤Reel size



Type	φD	φd	W	t
1608(0603) 2012(0805) 2016(0806) 3216(1206) 3225(1210)	180+0/−3 (7.09+0/−0.118)	60+1/−0 (2.36+0.039/−0)	10.0±1.5 (0.394±0.059)	2.5max (0.098max)
4516(1806) 4525(1810)			14.0±1.5 (0.551±0.059)	
4532(1812)	330±2.0 (12.99±0.080)	100±1.0 (3.94±0.039)	14.0±2.0 (0.551±0.080)	3.0max (1.181max)

Unit : mm(inch)

⑥Top tape strength



The top tape requires a peel-off force of 0.1 to 1.0N (0.315 inches wide) / 0.1 to 1.3N (0.472 inches wide) in the direction of the arrow as illustrated below.

Wire-wound Ferrite Bead Inductors for Power Lines LBMC/LBMG series for Telecommunications Infrastructure and Industrial Equipment
Wire-wound Ferrite Bead Inductors for Power Lines LMMC/LMMG series for Medical Devices classified as GHTF Class C (Japan Class III)

■RELIABILITY DATA

1. Operating Temperature Range	
Specified Value	−40℃～＋125℃ (Including self-generated heat)
Test Methods and Remarks	Including self-generated heat

2. Storage Temperature Range	
Specified Value	−40℃～＋85℃
Test Methods and Remarks	*Note: −5 to ＋40℃ in taped packaging

3. Impedance	
Specified Value	Within the specified range
Test Methods and Remarks	Measuring equipment : Impedance analyzer (HP4291A) or its equivalent Measuring frequency : 100±1 MHz

4. DC Resistance	
Specified Value	Within the specified range
Test Methods and Remarks	Four-terminal method Measuring equipment : Milliohm High-Tester 3226 (Hioki Denki) or its equivalent

5. Rated Current	
Specified Value	Within the specified range

6. Vibration	
Specified Value	Appearance : No significant abnormality Impedance change : Within ±30% of the initial value
Test Methods and Remarks	The test samples shall be soldered to the test board by the reflow. Then it shall be submitted to below test conditions.

Frequency	10～2000Hz	
Total Amplitude	5G	
Sweeping Method	20min(10→2000→10Hz)	
Time	X	4hours
	Y	
	Z	

7. Solderability	
Specified Value	90% or more of immersed surface of terminal electrode shall be covered with fresh solder.
Test Methods and Remarks	

Solder Temperature	245±5℃
Time	5sec
Preconditioning	Immersion into flux.
Immersing Speed	25mm/sec

8. Resistance to Soldering Heat	
Specified Value	Appearance : No significant abnormality Impedance change : Within ±30% of the initial value
Test Methods and Remarks	The test sample shall be exposed to reflow oven at 230℃ for 40 seconds, with peak temperature at 260＋0/−5℃ for 10 seconds, 2times. Test board material : Glass epoxy-resin Test board thickness : 1.6mm

9. Thermal Shock

Specified Value

Appearance : No significant abnormality
Impedance change : Within＋50/－10% of the initial value

Test Methods and Remarks

Conditions for 1 cycle

Step	Temperature (℃)	Duration (min.)
1	－40±3℃	30±3
2	Room Temperature	Within 3
3	125±2℃	30±3
4	Room Temperature	Within 3

Number of cycles : 1000
Mounting method : Soldering onto PC board
The measurement, after the test, shall be carried out the test sample has been left for 2 to 3 hours.

10. Resistance to Humidity (steady state)

Specified Value

Appearances : No significant abnormality
Impedance change : Within ±30% of the initial value

Test Methods and Remarks

The test samples shall be soldered to the test board by the reflow.
The test samples shall be placed in thermostatic oven set at specified temperature and humidity as shown in below table.

Temperature	40±2℃
Humidity	90～95%RH
Time	1000＋24/－0 hour

The measurement, after the test, shall be carried out the test sample has been left for 2 to 3 hours.

11. Loading under Damp Heat

Specified Value

Appearance No ignificant abnormality
Impedance change Within ±30% of the initial value

Test Methods and Remarks

The test samples shall be soldered to the test board by the reflow soldering.
The test samples shall be placed in thermostatic oven set at specified temperature, humidity, and applied the rated current continuously as shown in below table.

Temperature	85±2℃
Humidity	85%RH
Applied current	Rated current
Time	1000＋24/－0 hour

The measurement, after the test, shall be carried out the test sample has been left for 2 to 3 hours.

12. High Temperature Loading Test

Specified Value

Appearance : No significant abnormality
Impedance change : Within ±30% of the initial value

Test Methods and Remarks

The test samples shall be soldered to the test board by the reflow soldering.
The test samples shall be placed in thermostatic oven set at specified temperature and applied the rated current continuously as shown in below table.

Temperature	85±2℃
Applied current	Rated current
Time	1000＋24/－0 hour

The measurement, after the test, shall be carried out the test sample has been left for 2 to 3 hours.


13. Bending Strength

Specified Value

Appearance : No mechanical damage.

Test Methods and Remarks

The test samples shall be soldered to the test board by the reflow. As illustrated below, apply force in the direction of the arrow indicating until deflection of the test board reaches to 2 mm.
Warp : 2mm
Testing board : Glass epoxy-resin substrate
Thickness : 1.6mm



14. Adhesion of Electrode	
Specified Value	No separation or indication of separation of electrode.
Test Methods and Remarks	Applied force : 17.7N Duration : 10 sec.

Note on standard condition: ″standard condition″ referred to herein is defined as follows:
5 to 35℃ of temperature, 45 to 85% relative humidity and 86 to 106kPa of air pressure.
When there are questions concerning measurement results:
In order to provide correlation data, the test shall be conducted under condition of 20±2℃ of temperature, 60 to 70% relative humidity and 86 to 106kPa of air pressure. Unless otherwise specified, all the tests are conducted under the ″standard condition.″

Wire-wound Ferrite Bead Inductors for Power Lines LSMC/LSMG/LAMG/LCMC/LCMG/LBMC/LBMG/ LLMC/LLMG/LMMC/LMMG series

■PRECAUTIONS

1. Circuit Design

Precautions

◆Verification of operating environment, electrical rating and performance

1. A malfunction in medical equipment, spacecraft, nuclear reactors, etc. may cause serious harm to human life or have severe social ramifications. As such, any inductors to be used in such equipment may require higher safety and/or reliability considerations and should be clearly differentiated from components used in general purpose applications.
2. When inductors are used in places where dew condensation develops and/or where corrosive gas such as hydrogen sulfide, sulfurous acid, or chlorine exists in the air, characteristic deterioration may occur. Please do not use inductors under such environmental conditions.

◆Operating Current (Verification of Rated current)

1. The operating current including inrush current for inductors must always be lower than their rated values.
2. Do not apply current in excess of the rated value because the inductance may be reduced due to the magnetic saturation effect.

◆Temperature rise

Temperature rise of power choke coil depends on the installation condition in end products.
Make sure that temperature rise of power choke coils in actual end products is within the specified temperature range.

2. PCB Design

Precautions

◆Land pattern design

1. Please refer to a recommended land pattern.

3. Considerations for automatic placement

Precautions

◆Adjustment of mounting machine

1. Excessive impact load should not be imposed on the products when mounting onto the PC boards.
2. Mounting and soldering conditions should be checked beforehand.

Technical considerations

◆Adjustment of mounting machine

1. When installing products, care should be taken not to apply distortion stress as it may deform the products.

4. Soldering

Precautions

◆Wave soldering

1. Please refer to the specifications in the catalog for a wave soldering.

◆Reflow soldering

1. Please contact any of our offices for a reflow soldering, and refer to the recommended condition specified.

◆Lead free soldering

1. When using products with lead free soldering, we request to use them after confirming adhesion, temperature of resistance to soldering heat, etc. sufficiently.

◆Preheating when soldering

Heating : The temperature difference between soldering and remaining heat should not be greater than 150℃.
Cooling : The temperature difference between the components and cleaning process should not be greater than 100℃.

◆Recommended conditions for using a soldering iron


Put the soldering iron on the land-pattern.
Soldering iron's temperature – Below 350℃
Duration – 3 seconds or less
The soldering iron should not directly touch the inductor.

Technical considerations

◆Wave, Reflow, Lead free soldering

1. If products are used beyond the range of the recommended conditions, heat stresses may deform the products, and consequently degrade the reliability of the products.

【Recommended reflow condition】



◆Preheating when soldering

1. There is a case that products get damaged by a heat shock.

	◆Recommended conditions for using a soldering iron 1. If products are used beyond the range of the recommended conditions, heat stresses may deform the products, and consequently degrade the reliability of the products.

5. Handling	
Precautions	◆Handling 1. Keep the inductors away from all magnets and magnetic objects. ◆Setting PC boards 1. When setting a chip mounted base board, please make sure that there is no residual stress to the chip by distortion in the board or at screw part. ◆Breakaway PC boards (splitting along perforations) 1. When splitting the PC board after mounting inductors, care should be taken not to give any stresses of deflection or twisting to the board. 2. Board separation should not be done manually, but by using the appropriate devices. ◆Mechanical considerations 1. Please do not give the inductors any excessive mechanical shocks.
Technical considerations	◆Handling 1. There is a case that a characteristic varies with magnetic influence. ◆Setting PC boards 1. There is a case that a characteristic varies with residual stress. ◆Breakaway PC boards (splitting along perforations) 1. Planning pattern configurations and the position of products should be carefully performed to minimize stress. ◆Mechanical considerations 1. There is a case to be damaged by a mechanical shock.

6. Storage conditions	
Precautions	◆Storage 1. To maintain the solderability of terminal electrodes and to keep the packing material in good condition, temperature and humidity in the storage area should be controlled. ・Storage conditions Ambient temperature −5～40℃ Humidity Below 70% RH The recommended ambient temperature is below 30℃. Even under ideal storage conditions, solderability of products electrodes may decrease as time passes. For this reason, inductors should be used within 6 months from the time of delivery.
Technical considerations	◆Storage 1. Under a high temperature and humidity environment, problems such as reduced solderability caused by oxidation of terminal electrodes and deterioration of taping/packaging materials may take place.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TAIYO YUDEN:

LBMCA160808T180NG LBMCA160808T230NG LBMCA201208T210NG LBMCA201208T330RG LBMCA321611T380NG LBMCA321611T600RG LBMCA451611T560NG LBMCA451611T900RG LBMCC160808T220NG LBMCC160808T280NG LBMCC201208T250NG LBMCC201208T420RG LBMCC321611T480NG LBMCC321611T800RG LBMCC451611T111RG LBMCC451611T720NG LBMCG201208T8R0NG LBMCG321611T160NG LBMCG451611T230NG LBMGA160808T101RG LBMGA160808T102RG LBMGA160808T151RG LBMGA160808T221RG LBMGA160808T331RG LBMGA160808T470RG LBMGA160808T471RG LBMGA160808T600RG LBMGA160808T601RG LBMGA201208T121RG LBMGA201208T221RG LBMGA201208T331RG LBMGA201208T800RG LBMGA201616T121NG LBMGA201616T251NG LBMGA321616T221NG LBMGA321616T501NG LBMGA322525T102NG LBMGA322525T202NG LBMGA322525T601NG LBMGA451616T851NG LBMGA452525T102NG LBMGA452525T162NG LBMGG160808T121RG LBMGG160808T221RG LBMGG160808T300RG LBMGG160808T331RG LBMGG160808T471RG LBMGG160808T600RG LBMGG160808T601RG