

HSF RoHS FILE NO :E362810

SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Phosphor Bronze
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Standard: PA6T
Max.Processing Temp: 230°C for 30−60 seconds
(260°C for 10 seconds)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)




Ordering Information


2434 02 XX X X XX M U X 0X

No.of Pins Per Row	Insulator Material Option	Post	Contact Plating	Packing
2−50	C=BK−PA6T E=BK−PA9T F=BK−LCP	W=With Post N=W/O Post	G1:Gold Flash G3:2U" Gold G4:3U" Gold G5:5U" Gold S0:Gold Flash/Tin SN:Tin	A=Tray T=Tube P=Tube+Cap R=Reel+Cap M=Reel+Mylar





W= With Post



N= W/O Post

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2022.03.09	NEW DRAWING	

OPERATION		DRAW	Wei Chen	22.03.09
X.X	±0.30			
X.XX	±0.20	CHECK		
X.XXX	±0.10			
Angle	±3°	APPROVE		
DIM	TOL			

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

JILN® 深圳市锦凌电子有限公司
SHENZHEN JINLING ELECTRONIC CO.,LTD
Tel：86-755-2997-5806/5802 Fax：86-755-2997-5992

PART NO.	243402XXXXXXMUX0X
TITLE:	1.27PF 2xNPin H3.4 带夹持盖