


HX65176-S High speed bus transceiver

The HX65176-s is a high-speed RS485/RS-422 transceiver circuit that operates on a +5V power supply with half-duplex functionality. It features one driver and one receiver, achieving transmission speeds of up to 10Mbps. The circuit includes $\pm 15\text{KV}$ ESD protection to safeguard the chip from electrostatic discharge. Both the driver and receiver have enable pins (DE and RE). When these pins are disabled, the output enters a high-resistance state. Additionally, the HX65176-s incorporates a fail-safe circuit that ensures correct output in open or short circuits at the receiver input. The receiver's input impedance is 1/8 unit load, allowing for a maximum of 256 transceivers on the same bus.



SOP-8

Characteristic


- Tri state output.
- Electrostatic Discharge (ESD): A/B $\pm 15\text{KV}$, compliant with Human Body Mode (HBM) standards.
- The bus allows up to 256 transceivers to be connected.
- Maximum data speed of 10 Mbps
- Adopting SOP8 encapsulation.

Application

- Industrial control
- RS485/RS422
- interface Industrial motor drive
- Automated HVAC system

Chip Pin Description

ID	NUME	Function
1	RO	Receiver data output
2	$\overline{\text{RE}}$	The receiver output is effective at low levels and high when high.
3	DE	SET: High valid when DE low, output high
4	DI	Drive data input
5	GND	Ground
6	A	Driver data output, receiver data input
7	B	Driver data output, receiver data input
8	Vcc	power supply



SOP-8

Driver Truth Table


Input	Enable	Output	
DI	DE	A	B
H	H	H	L
L	H	L	H
X	L	Z	Z

Receiver Truth Table

Input			Output
$\overline{\text{RE}}$	DE	A-B	RO
L	X	$\geq -50\text{mV}$	H
L	X	$\leq -200\text{mV}$	L
L	X	open circuit	H
L	X	short circuit	H
H	H	X	Z
H	L	X	Z


Dc Electrical Parameter							
Limiting Parameter							
SYMBOL	PARAMETER NAME		MIN	MAX		UNIT	
VCC	Supply voltage			+6.0		V	
DE, RE	Control input voltage		-0.5	+6.0		V	
DI	Drive input voltage		-0.5	+6.0		V	
A,B	Drive output voltage/receive input voltage		-7.0	+12.0		V	
RO	Receiving output voltage		-0.3	VCC+0.3		V	
TSTG	Storage temperature range		-55	+150		°C	
TOP	Operating temperature range		-40	+85		°C	
TMOP	Maximum operating temperature range		-55	+125		°C	
P _D	SOP-8 (+70°C or above)			470		mW	
T _L	Solder temperature (10 seconds)			+300		°C	
DC characteristics (unless otherwise specified, Vcc=5V ± 5%, TA=25 °C) 2							
ARGUMENT	SYMBOL	Test condition		MIN	TYP	MAX	UNIT
Working voltage range	VCC			4.5		5.5	V
Driver differential output (no load)	VOD1	-		-		5	V
Driver differential output (with load)	VOD2	R=54ΩorR=27Ω Figure 1		1.5		-	V
AVDV_DO_Driver1	ΔV _{OD}			-		0.2	V
Driver common mode output voltage	VOC			1		3	V
ΔVCOM_DRV1	ΔV _{OC}					0.2	V
Input high voltage	VIH	DE,RE,DI		2			V
Input undervoltage	VIL	DE,RE,DI				0.8	V
Input current	IIN1	DE,RE,DI				±2	uA
Input current (A, B)	IIN2	DE=0V,Vcc=5V	V _{IN} =5V		40	90	uA
			V _{IN} =0V		60	100	
Receiver differential input threshold voltage	VTH	-7V ≤ V _{CM} ≤ +12V		-200		-50	mV
Receiver input delay	ΔV _{TH}				25		mV
Receiver output high level	VOH	I _O =-8mA		4			V
Receiver output low level	VOL	I _O =8mA				0.4	V
RT-HI-OC	IOZR	0.4V ≤ V _O ≤ 2.4V				1	uA
Receiver input impedance	RIN	-7V ≤ V _{CM} ≤ +12V		96			kΩ
No load operating current	ICC	no-load	DE = Vcc		480	600	uA
		RE=DI=GND or Vc	DE=GND		450	600	uA
Receiver output short-circuit current	IOSR	c 0V ≤ VRO≤VCC				95	mA
ESD protection		Between A/B, human body mode		±8	±15		kV
Switch characteristics not specified otherwise Vcc=5V ± 5%, TA=25°C							
Parameter	Symbol	Test Conditions		MIN	TYP	MAX	UNIT
Drive input to output	tDPLH	R _{DIFF} =50Ω C _{L1} =C _{L2} =100Pf Figure3, 5			34	60	nS
	tDPHL				34	60	nS
Driver output offset tDPLH – tDPHL	tDSKEW				-2.5	±10	nS
Drive up and down time	tDR				10	25	nS
	tDF				10	25	nS
Driver enables high output	tDZH	C _L 00pF Figure4,6 S2 close				150	nS
Driver enables output to be low	tDZL	C _L =100pF Figure4,6 S1 close				150	nS
Drive from low to off	tDLZ	C _L =15pF Figure4,6 S1 close				100	nS
Drive from high to off	tDHZ	C _L =15pF Figure4,6 S2 close				100	nS
Receiver input to output	tRPLH	V _{ID} ≥ 2.0V;V _{ID} Rising and falling				150	nS
	tRPHL					150	nS
Differential receiver offset	tRSKEW	time≤15nS Figure 7,9			0	±10	nS
The receiver stays on until output is low	tRZL	C _L =100pF Figure 2,8			20	50	nS
Enable the receiver to output high	tRZH	C _L =100pF Figure 2,8			20	50	nS
Receiver from low to off	tRLZ	C _L =100pF Figure 2,8			20	50	nS
Receiver from high to off	tRHZ	C _L =100pF Figure 2,8			20	50	nS

Typical Application





Packaging and packaging

SOP8 (Package Outline Dimensions)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
B	0.330	0.510	0.013	0.020
C	0.190	0.250	0.007	0.010
D	4.780	5.000	0.188	0.197
E	3.800	4.000	0.150	0.157
E1	5.800	6.300	0.228	0.248
e	1.270TYP		0.050TYP	
L	0.400	1.270	0.016	0.050
θ	0°		8°	



Packaging Method	Number
Braid	2500PCS/Disk