

备注(NOTE): 1 材质:






- 1.1 胶芯: LCP UL94 V-0
- 1.2 端子: (C2680, ; 镍底, 镀金 0.5U)
- 1.3 外壳: 不锈钢 201 - 表面镀镍 50U

2. 电气特性:

- 2.1 接触区: 接触电阻 30mQMax, 允许 10mΩ 变化量, 测试条件: 20mv, 100mA 下测量,
- 2.2 额定电流: 最大 3A
- 2.3 额定电压: 5V.
- 2.4 耐电压: 100VAC.
- 2.5 绝缘电阻: 至少 100兆欧

3. 机械性能:

- 3.1 插入力: 0.5-2.0Kg
- 3.2 拔出力: 0.8-2.0Kg
- 3.3 插拔次数: 5000+.
4. 工作环境: -20℃ to +85℃
- 4.1 盐雾测试: 24H



PIN ASSIGNMENTS

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co., Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: USB-type C 6pin 母座 沉板 0.8MM - 成品
			PAR TYPE-C-335-WFRSC08L65
DECIMALS:	ANGLES:	CUSTOMER COPY	DWN
.X: ±0.35	.X': ±2'		CHKD
.XX: ±0.25	.XX': ±1'		APVD
.XXX: ±0.15			SCALE 1:1 UNIT: MM
		SIZE: A4	UNIT: MM
		SHEET: 1F1	REV: A