




Product NO.

RHT-634-1386



ISSUE	DESCRIPTION	DWN	DATE	APPROVEN
RI.0	First issue	Gavin	2020/12/09	JIM. KING

NOTES:


- Rated voltage/current : 3pin: 250V/4A
4pin: 250V/4A
5pin: 60V/4A
8pin: 30V/2A
- Withstanding voltage : 3,4pin: AC1500V/1 Min
5pin: AC1120V/1 Min
8pin: AC500V/1 Min
- Levels of protection: IP67
- Connection mode: Soldering
- Operating temperature: -40℃ ~+80℃
- RoHS Compliance




Front View




Rear View

RECOMMENDED
MOUNTING HOLE


Pin Assignments Front View




3Pin



4Pin




5Pin



8Pin

5	Contacts	Brass	Gold	3-8
4	Nut M16*1.5	Brass	Nickel	1
3	O-Ring	Rubber		1
2	Body	Brass	Nickel	1
1	Insulator	PA66	Black	1
NO	Description	Material	Finish	Qty

-TOLERANCES-
UNLESS OTHERWISE
SPECIFIEDdosinconn DOSIN INDUSTRIAL(HK)CO.,LTD
江门市德索连接器有限公司
Jiangmen Dosin Connector Co., LTDWeb: http://www.dosinconn.com
Dosin2005@dosin-china.com
Tel: (0086) 769-81153906
Fax: (0086) 769-81875836

PART DESCRIPTION:

Male, M12, Back Mount Connector

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS ARE:
0.5 ~ 8mm ± 0.20mm
8 ~ 30mm ± 0.25mm
30 ~ 120mm ± 0.30mm

Appr: JIM. KING

P/N: RHT-634-1386

Check:

Date

Scale

Unit

Type

Page

Draw: Gavin

2019.12.09

Free

MM

Z

1/1