



	UL	IEC
1. Rated Voltage :	300V	320V
2. Rated Current :	15A	20A
3. Withstanding Voltage :	AC1600V/1Min.	
4. Operating Temperature :	-40°C~+105°C	
5. RoHS Compliance		
6. Safety Approval :	cULus CE	
7. ★ " " is the key quality control point		

① ② ③ ④ ⑤ ⑥

① Series NO. ④ 1 Single Pitch
 2 Double Pitch

② Pitch ⑤ Color: 1 Grey
 2 Blue
 3 Black
③ Poles 4 Green
02 02Contacts 5 Orange
03 03Contacts 6 Red
... 7 Transparent
24 24Contacts 8 Yellow
 9 White

⑥ Customer Request: 100--Standard

Total Pitch Tolerances in mm										Nominal dimension range in mm										$\perp$		$\div$		$-$		$//$									
over	0	30	53	70	90	over	115	over	150	over	250	over	350	over	0	30	53	70	90	115	over	150	over	200	250	320	over	0	10	all	over	0	100	over	150
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	
0	30	53	70	90	115	150	250	350	500	0	30	53	70	90	115	150	200	250	320	0	10	all	over	0	100	over	150								
± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.4	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.4	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5												

				OPERATION		SCALE		Fit		东莞市宇熙精密连接器有限公司 www.yxcon.com Dongguan Yuxi Electronic Co.,Ltd.		
				X.X	±0.25	UNIT		MM				
				X.XX	±0.20	SIZE	A4	DESIGN	赵文品2024.10.10	PART NO	2EGTR-5.08-XXP-XX-100	
				X.XXX	±0.10							
				Angle	±3°	SHEET	1/1	CHECK		TITLE		
REV	DATE	SYMBOL	MODIFICATION DESCRIPTION	DIM	TOL	PROJ.		APPROVE		Customer No.		