





LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00		J	REVISED PER ECO-14-011808	09AUG2014	AP	SB



- CONNECTOR ACCEPTS SIZE 20 DF PIN CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
- CONNECTOR COMPLIES WITH 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: GLASS-FILLED PBT OR GLASS-FILLED NYLON, UL94V-0 RATED. COLOR: BLACK
- SHELLS: STEEL PER ASTM A109.
- TIN OR TIN-LEAD PLATED OVER COPPER UNDERPLATE.
- TIN PLATED OVER COPPER UNDERPLATE.

OBSOLETE SUPERSEDED BY 207464-2 SUPERSEDED BY 207464-2 SUPERSEDED BY 207464-7	STANDARD	6	NO	.120	207464-7
	SMALL PACK	6	YES	.120	207464-6
	STANDARD	5	YES	.154	207464-4
	STANDARD	5	NO	.154	207464-3
	STANDARD	6	YES	.120	207464-2
SUPERSEDED BY 207464-7	STANDARD	5	NO	.120	207464-1
	PACKAGING TYPE	SHELL FINISH	GROUNDING INDENTS	A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S.WELDON 7-19-85	 TE Connectivity				
		CHK J.GERACE 7-29-85					
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD —	NAME PLUG CONNECTOR, SIZE 3, 25 POSITION, AMPLIMITE™ HDP —				
	0 PLC ± —	PRODUCT SPEC —					
	1 PLC ± —	—					
	2 PLC ± —	APPLICATION SPEC					
	3 PLC ± .005	—					
4 PLC ± —	ANGLES ± ±	—	SIZE A2	CAGE CODE 00779	DRAWING NO C=207464	RESTRICTED TO —	
MATERIAL SEE NOTES	FINISH SHELLS: SEE TABLE	WEIGHT —					
CUSTOMER DRAWING			SCALE 4:1	SHEET 1 of 1	REV J		